Copyright is owned by the Author of the thesis. Permission is given for a copy to be downloaded by an individual for the purpose of research and private study only. The thesis may not be reproduced elsewhere without the permission of the Author.

Investigating Downdraft Gasification of Biomass

A thesis presented in partial fulfilment of the requirements for the degree of

Doctor of Philosophy in Physics

Massey University, Palmerston North, New Zealand.

Donna Louise Giltrap 2002

Abstract

Gasification of biomass is a potential source of renewable energy. Downdraft gasifiers are comparatively cheap and can produce gases with low tar content. We constructed a simple, phenomenological model of downdraft gasification which we compared to both previously published data and our own experimental results. The steady-state gas compositions predicted by the model were quite close to those found experimentally, although the model tended to over-predict the amount of methane in the dry product gas. The steady-state gas composition predicted depended upon the conditions assumed at the top of the gasifier.

The experimental part of this investigation looked at the effect of the air flow rate into the gasifier and the length of the gasifier bed. However, the uncertainties in the experimental measurements were too large to determine whether the experimental results followed the same trends as predicted by the model.

The gasifier was run successfully using both 18.7% moisture content pine chips and 12.3% moisture content walnut shells (weight percentage, dry basis) as fuel. Both fuel types produced dry exit gases of similar compositions.

Acknowledgements

This project received funding from the Institute of Fundamental Sciences Graduate Research Fund and the Massey University Research Equipment Fund.

I would also like to thank the following for their contributions towards this project:

- Bill Dwyer of Dwyer Technical Services for his help in developing the gasifier ignition system and for the loan of a gas bottle and fittings.
- The Institute of Fundamental Sciences specialist services staff for their help in manufacturing, altering and repairing the experimental apparatus.
- The Fielding Lumber Co. for the donation of some freshly cut pine chips.
- The Institute of Technology and Engineering for the loan of a digital anemometer and the use of the gas chromatograph.
- Malcolm Harbrow for allowing himself to be drafted to help carry equipment and fuel.
- My supervisors Geoff Barnes and Robert McKibbin.

Table of Contents

| ABSTRACTii |
|---|
| ACKNOWLEDGEMENTSiii |
| LIST OF FIGURES AND TABLES vii |
| 1. INTRODUCTION1-1 |
| 1.1 The World Energy Situation |
| New Zealand Energy Usage1-3 |
| 1.2 GASIFICATION |
| Downdraft1-7 |
| Updraft |
| Fluidised Bed1-9 |
| 1.3 REVIEW OF RELATED RESEARCH |
| (A) Electricity Production Using Gasification |
| (B) Gasification of Biomass1-10 |
| (C) Modelling Gasification1-11 |
| 1.4 THESIS ORGANISATION |
| 2. EXPERIMENTAL APPARATUS2-1 |
| 2.1 Gasifier Ignition System |
| 2.2 TRANSDUCERS AND CALIBRATION |
| (A) Temperature |
| (B) Inlet Air Flow Rate2-5 |
| (C) Exit Gas Flow Rate2-8 |
| (D) Pressure Gradient across bed2-11 |
| (E) Fuel Moisture Content2-12 |
| (F) CO detector |
| 2.3 Gas Collection and Analysis |
| (A) Gas Sampling2-13 |
| (B) Gas Chromatograph2-13 |
| 3. STEADY STATE AND TIME DEPENDENT MODELS 3-1 |

| 3.1-DIMENSIONAL STEADY-STATE MODEL | 3-2 |
|--|------|
| (A) Reaction Rates | 3-2 |
| (B) Mass and Energy Balances | |
| (C) Model Sensitivity to Initial Conditions | |
| Varying Initial Temperature | |
| Varying Initial Pressure | |
| Varying Initial Velocity and C_{RF} | |
| Varying Initial CO ₂ | 3-13 |
| Varying Initial CO and CH₄ | |
| Varying Initial H ₂ | |
| Varying Initial H ₂ O | |
| (D) Initial Values | |
| Initial Gas Concentrations. | |
| Initial Gas Temperature | |
| Char Reactivity Factor (C_{RF}) | |
| Pyrolysis Fraction | |
| (E) Comparison with Experimental results | |
| 3.2 I-DIMENSIONAL STEADY STATE MODEL WITH COMBUSTION REACTIONS | |
| 3.3 TIME DEPENDENT MODEL | |
| (A) Model Construction | 3-29 |
| (B) Agreement with Steady State Model | |
| 3.4 CONCLUSION | |
| 4. EXPERIMENTAL RESULTS | 4-1 |
| 4.1 PERFORMANCE OF GASIFIER RUN IN BATCH MODE | 4-1 |
| (A) Mass and Energy Balances of Gasifier | |
| 4.2 EFFECT OF VARYING BED LENGTH | 4-5 |
| (A) Exit Gas Temperature | |
| (B) Exit Gas Composition | |
| (C) Mass and Energy Balance of Gasifier | 4-10 |
| (D) Summary | 4-11 |
| 4.3 EFFECT OF VARYING AIR FLOW RATE | |
| (A) Exit Gas Temperature | 4-12 |
| (B) Exit Gas Composition | 4-15 |
| (C) Mass and Energy Balances of Gasifier | 4-18 |
| (D) Summary | 4-22 |

| 4.4 EFFECT OF DIFFERENT FUEL TYPES | |
|---|--|
| (A) Exit Gas Temperature | |
| (B) Exit Gas Composition | |
| (C) Mass and Energy Balances of the Gasifier | |
| (D) Summary | |
| 4.5 CONCLUSION | |
| 5 COMPARING EXPERIMENTAL RESULTS WITH MODEL PREDICTIONS | |
| | |
| 5.1 MODEL WITHOUT METHANE COMBUSTION | |
| (A) Effect of Varying Air Flow Rate | |
| (B) The Effect of Varying Bed Length | |
| (C) Summary | |
| 5.2 MODEL INCLUDING METHANE COMBUSTION REACTIONS | |
| (A) The Effect of Varying the Air Flow | |
| (B) The Effect of Varying Bed Length5-14 | |
| (C) Summary5-17 | |
| 6 CONCLUSION | |
| APPENDIX A: JUSTIFICATION OF THE IDEAL GAS APPROXIMATION. 7-1 | |
| APPENDIX B: EQUILIBRIUM CONSTANTS FOR REACTIONS | |
| APPENDIX C: MATLAB SCRIPTS | |
| REFERENCES 10-1 | |

List of Figures and Tables

| FIGURE 1.1: NEW ZEALAND ENERGY CONSUMPTION BY FUEL TYPE FOR THE CALENDAR |
|--|
| YEAR 2001 |
| Figure 1.2: New Zealand CO_2 emissions by sector for the calendar year 2001 |
| |
| FIGURE 1.3: NEW ZEALAND ELECTRICITY GENERATION FOR THE YEAR ENDED MARCH |
| 2002 |
| |
| FIGURE 1.4: SCHEMATIC OF A TYPICAL DOWNDRAFT GASIFIER |
| FIGURE 1.5: SCHEMATIC OF A TYPICAL UPDRAFT GASIFIER |
| FIGURE 1.6: SCHEMATIC OF A TYPICAL FLUIDISED BED GASIFIER |
| FIGURE 2.1: DOWNDRAFT GASIFIER CONFIGURATION |
| FIGURE 2.2: CALIBRATION OF N-TYPE THERMOCOUPLE USED IN EXPERIMENTS2-5 |
| FIGURE 2.3: VOLUME FLOW RATE OF AIR OUT OF VACUUM CLEANER VS THE SETTING OF |
| THE VARIAC VARIABLE TRANSFORMER ATTACHED TO THE VACUUM CLEANER POWER |
| SUPPLY |
| FIGURE 2.4: AIR SPEED AT VACUUM CLEANER INLET VS. THE VOLUME FLOW RATE |
| OUTPUT OF THE VACUUM CLEANER |
| FIGURE 2.5: AIR FLOW RATE PRODUCED BY VACUUM CLEANER AT DIFFERENT VARIAC |
| SETTINGS WHEN OPERATING AGAINST ATMOSPHERIC PRESSURE AND WHEN |
| CONNECTED TO AN OPERATING GASIFIER |
| FIGURE 2.6: PRESSURE DROP ACROSS THE VENTURI CONSTRUCTION PLOTTED AS A |
| FUNCTION OF VOLUME FLOW RATE AND TEMPERATURE |
| FIGURE 2.7: PRESSURE GRADIENT AS A FUNCTION OF SUPERFICIAL GAS VELOCITY FOR |
| GASIFIER BEDS OF WOOD CHIPS AND WALNUT SHELLS |
| FIGURE 2.8: LOG OF THE NORMALISED CONCENTRATION OF H_2 REMAINING IN SAMPLE VS |
| TIME |
| TABLE 3.1: NET RATE OF PRODUCTION OF THE DIFFERENT GASEOUS SPECIES BY |
| CHEMICAL REACTIONS IN TERMS OF THE RATES OF REACTIONS 1 - 4 |
| TABLE 3.2: INITIAL VALUES USED IN SIMULATIONS TO TEST THE MODEL SENSITIVITY.3-8 |

| FIGURE 3.2: THE EFFECTS OF CHANGING THE INITIAL PRESSURE ON (A) THE GASIFIER |
|--|
| TEMPERATURE PROFILE, (B) THE DRY GAS HHV and (C) the molar flux of DRY |
| GAS PREDICTED |
| FIGURE 3.3: THE EFFECTS OF VARYING SUPERFICIAL GAS VELOCITY ON (A) THE GASIFIER |
| TEMPERATURE PROFILE AND (B) THE DRY GAS HHV PREDICTED |
| FIGURE 3.4: The effects of varying the C_{RF} on (A) the temperature profile of |
| THE REDUCTION ZONE AND (B) THE DRY GAS HHV PREDICTED |
| FIGURE 3.5: The effects of varying initial CO_2 concentration on (A) the |
| TEMPERATURE PROFILE OF THE REDUCTION ZONE AND (B) THE DRY GAS HHV |
| PREDICTED |
| FIGURE 3.6: THE EFFECTS OF VARYING THE INITIAL CONCENTRATION OF CO ON (A) THE |
| TEMPERATURE PROFILE OF THE REDUCTION ZONE AND (B) THE DRY GAS HHV |
| PREDICTED |
| FIGURE 3.7: The effects of varying initial CH_4 concentration on (A) the |
| TEMPERATURE PROFILE IN THE REDUCTION ZONE AND (B) THE DRY GAS HHV |
| PREDICTIONS |
| FIGURE 3.8: The effects of varying initial H_2 concentration on (A) the |
| TEMPERATURE PROFILE OF THE REDUCTION ZONE AND (B) THE DRY GAS HHV |
| PREDICTIONS |
| Figure 3.9: The effects of varying the initial H_2O concentration on (A) the |
| TEMPERATURE PROFILE OF THE REDUCTION ZONE, AND (B) THE DRY GAS HHV |
| PREDICTIONS |
| TABLE 3.3: COMPOSITION OF PINUS RADIATA WOOD |
| TABLE 3.4: CALCULATED COMPOSITION OF THE VOLATILE COMPONENT OF PINUS |
| RADIATA WOOD |
| FIGURE 3.10: GASIFIER TEMPERATURE PROFILES PREDICTED BY THE MODEL USING |
| DIFFERENT C_{RF} VALUES |
| FIGURE 3.11: N_2 CONCENTRATIONS IN DRY GAS PREDICTED BY MODEL USING DIFFERENT |
| F_P VALUES |
| TABLE 3.5: PARAMETERS USED IN EXPERIMENTAL DOWNDRAFT GASIFICATION AND IN |
| THE MODEL SIMULATION |
| FIGURE 3.12: DRY EXIT GAS COMPOSITION PREDICTED BY THE STEADY STATE MODEL |
| COMPARED WITH THE EXPERIMENTAL RESULTS OF CHEE (1987) AND SENELWA |
| (1997) |

FIGURE 3.12: DRY EXIT GAS COMPOSITION PREDICTED BY THE STEADY STATE MODEL COMPARED WITH THE EXPERIMENTAL RESULTS OF CHEE (1987) AND SENELWA FIGURE 3.13: DRY EXIT GAS COMPOSITION PREDICTED BY THE STEADY STATE MODEL. COMPARED WITH THE EXPERIMENTAL RESULTS OF CHEE (1987) AND SENELWA **TABLE 3.6:** NET RATE OF PRODUCTION OF THE DIFFERENT GASEOUS SPECIES BY FIGURE 3.14: DRY EXIT GAS COMPOSITION PREDICTED BY MODEL INCLUDING METHANE. COMBUSTION REACTION COMPARED WITH EXPERIMENTAL RESULTS FROM CHEE FIGURE 3.15: DRY EXIT GAS COMPOSITION PREDICTED BY MODEL INCLUDING METHANE COMBUSTION REACTION AND ASSUMING PYROLYSIS GAS CONSISTS OF CO_2 , CH_4 and H₂O, COMPARED WITH EXPERIMENTAL RESULTS FROM CHEE (1987) AND SENELWA FIGURE 4.1: EXIT GAS TEMPERATURE PLOTTED AGAINST TIME FOR GASIFIER OPERATED FIGURE 4.2: COMPOSITION (BY VOLUME FRACTION) OF DRY EXIT GAS SAMPLES TAKEN AT TABLE 4.1: VALUES OF PARAMETERS A, B, C, AND D DERIVED FROM EXPERIMENTAL FIGURE 4.3: EXIT GAS TEMPERATURE VS TIME FOR GASIFIER BED LENGTHS (A) 10CM. (B) FIGURE 4.4: "STEADY-STATE" EXIT GAS TEMPERATURE OF GASIFIER VS BED LENGTH.... 4-7 FIGURE 4.5: O2 CONCENTRATION FOR GASIFIER RUNNING ON PINE CHIPS AT NEAR FIGURE 4.6: COMPOSITION OF DRY EXIT GAS VS TIME FOR BED LENGTHS (A) 0.10 FIGURE 4.7: AVERAGE COMPOSITION OF THE DRY EXIT GAS DURING "STEADY-STATE" **TABLE 4.2:** VALUES OF PARAMETERS A, B, C, AND D DERIVED FROM EXPERIMENTAL MEASUREMENTS OF STEADY-STATE DOWNDRAFT GASIFIER PRODUCT GAS FOR

| FIGURE 4.8: GAS EXIT TEMPERATURE VS TIME FOR GASIFIER USING PINE CHIPS AS FUEL. |
|---|
| |
| TABLE 4.3: TIME INTERVALS FOR WHICH THE GASIFIER OPERATION WAS APPROXIMATELY |
| STEADY-STATE |
| FIGURE 4.9: EXIT GAS TEMPERATURE DURING STEADY-STATE OPERATION VS THE MOLAR |
| FLOW RATE OF AIR INTO THE INLET |
| FIGURE 4.10: MEASURED GAS CONCENTRATIONS (EXPRESSED AS VOLUME |
| PERCENTAGES) VS TIME FOR GASIFIER USING PINE CHIPS AS FUEL |
| FIGURE 4.11: STEADY-STATE COMPOSITION OF DRY EXIT GAS VS THE FLOW RATE OF AIR |
| INTO THE GASIFIER |
| TABLE 4.4: VALUES OF PARAMETERS A, B, C, AND D DERIVED FROM EXPERIMENTAL |
| MEASUREMENTS OF STEADY-STATE DOWNDRAFT GASIFIER PRODUCT GAS FOR |
| VARIOUS AIR FLOW RATES |
| TABLE 4.5: ENERGY BALANCE FOR GASIFICATION OF A MOLE PINE CHIPS WITH DIFFERENT |
| AIR INFLOW RATES |
| FIGURE 4.12: ENERGY BALANCES FOR GASIFICATION OF PINE CHIPS AT AIR FLOW RATES |
| OF (A) 0.22 ± 0.03 MoL/s, (B) 0.32 ± 0.06 MoL/s and (C) 0.6 ± 0.1 MoL/s4-20 |
| TABLE 4.6: RATE OF EXIT GAS CHEMICAL ENERGY PRODUCTION FOR DIFFERENT AIR |
| FLOW RATES |
| FIGURE 4.13: TEMPERATURE OF EXIT GAS VS TIME FOR GASIFIER OPERATING ON WALNUT |
| SHELLS |
| FIGURE 4.14: COMPOSITION OF DRY EXIT GAS. GASIFIER OPERATING WITH WALNUT |
| SHELLS FOR FUEL, BED LENGTH = 10 ± 1 CM |
| FIGURE 4.15: COMPOSITION OF STEADY-STATE DRY EXIT GAS FOR GASIFIER RUN ON PINE |
| CHIPS AND WALNUT SHELLS |
| TABLE 4.7: COMPOSITION OF WALNUT SHELLS 4-25 |
| TABLE 4.8: VALUES OF PARAMETERS A, B, C, AND D DERIVED FROM EXPERIMENTAL |
| MEASUREMENTS OF STEADY-STATE DRY EXIT GAS COMPOSITION FOR DOWNDRAFT |
| GASIFIER OPERATED USING WALNUT SHELLS AS FUEL |
| FIGURE 5.1: THE DRY EXIT GAS COMPOSITION FOUND FOR A GASIFIER RUN USING AN AIR |
| Flow rate of 0.22 ± 0.03 mol.s ⁻¹ and BED length of 0.10 ± 0.01 m compared |
| TO THE MODEL PREDICTION |

| TABLE 5.1: SUPERFICIAL GAS VELOCITIES CORRESPONDING TO THE DIFFERENT AIR FLOW |
|--|
| RATES |
| FIGURE 5.2: EXPERIMENTAL RESULTS AND MODEL PREDICTIONS OF THE EXIT GAS |
| TEMPERATURE VS INITIAL GAS VELOCITY |
| FIGURE 5.3: MODEL PREDICTIONS AND EXPERIMENTAL MEASUREMENTS OF THE MOLAR |
| FRACTION OF (A) N_2 , (B) CO_2 , (C) CO , (D) CH_4 and (E) H_2 in the Dry exit gas |
| AS THE INITIAL SUPERFICIAL GAS VELOCITY IS VARIED |
| FIGURE 5.4: EXPERIMENTAL MEASUREMENT AND MODEL PREDICTION OF THE STEADY- |
| STATE EXIT GAS TEMPERATURE VS GASIFIER BED LENGTH |
| FIGURE 5.5: MODEL PREDICTIONS AND EXPERIMENTAL MEASUREMENTS OF THE MOLAR |
| FRACTION OF (A) N_2 , (B) CO_2 , (C) CO , (D) CH_4 and (E) H_2 in the Dry exit gas |
| AS THE BED LENGTH WAS VARIED |
| FIGURE 5.6: EXPERIMENTAL RESULTS AND MODEL PREDICTIONS OF THE STEADY-STATE |
| EXIT GAS TEMPERATURE VS INITIAL GAS VELOCITY |
| FIGURE 5.7: MODEL PREDICTIONS AND EXPERIMENTAL MEASUREMENTS OF THE MOLAR |
| FRACTION OF (A) N_2 , (B) CO_2 , (C) CO , (D) CH_4 and (E) H_2 in the dry exit gas |
| AS THE INITIAL SUPERFICIAL GAS VELOCITY IS VARIED |
| FIGURE 5.8: EXPERIMENTAL MEASUREMENT AND MODEL PREDICTION OF THE STEADY- |
| STATE EXIT GAS TEMPERATURE VS GASIFIER BED LENGTH |
| FIGURE 5.9: MODEL PREDICTIONS AND EXPERIMENTAL MEASUREMENTS OF THE MOLAR |
| FRACTION OF (A) N_2 , (B) CO_2 , (C) CO , (D) CH_4 and (E) H_2 in the Dry exit gas |
| AS THE BED LENGTH WAS VARIED |
| TABLE 7.1: CORRECTION TERMS TO THE IDEAL GAS EQUATION FOR GASES WITH $T = 900$ |
| K, $V_M = 7.38 \times 10^{-2} \text{ m}^3/\text{MOL}$, $P = 101,300 \text{ PA}$ |
| TABLE 7.2: CORRECTION TERMS TO THE IDEAL GAS EQUATION FOR GASES IN GASIFIER |
| WITH $T = 900$ K, $V_M = 7.38 \times 10^{-3} \text{ m}^3/\text{MOL}$, $P = 1,013,000$ PA7-3 |
| FIGURE 8.1: THE LOG OF THE EQUILIBRIUM CONSTANTS FOR REACTIONS 1-5 PLOTTED |
| AGAINST THE RECIPROCAL OF THE TEMPERATURE |
| TABLE 8.1: FORMULAE USED TO CALCULATE EQUILIBRIUM CONSTANTS OF REACTIONS AT |
| DIFFERENT TEMPERATURES |